

SAFE & SECURE DIESEL STORAGE

AGRICULTURAL | COMMERCIAL | HAULAGE

Durable & Stable MDPE Design



Manufactured in the UK, our range of modern Bunded Diesel Dispensing Tanks are suitable for a variety of applications including agriculture, construction, mining and road haulage.



Compatible

10 Year Conditional Registered Warranty*



www.harlequinplastics.co.uk













CE



DIESEL TANKS RANGE

Harlequin range of Bunded Diesel Dispensing Tanks are manufactured to exceed the most demanding technical, environmental and regulatory requirements. The range includes fuel stations and fuel points from 1300 to 9250 litres.

Fuel Stations are high specification diesel tanks offering a quick and easy, safe and secure on-site fuel storage solution for smaller commercial, industrial and agricultural requirements.

Fuel Points are straightforward diesel storage and dispensing systems featuring the same high-quality mouldings and materials as fuel stations best suited for farms, haulage & businesses.





FUEL POINTS & FUEL STATIONS



1300 Litre Slimline Fuel Station / Fuel Point



1400 Litre Fuel Station / Fuel Point



2500 Litre Slimline Fuel Station / Fuel Point





2500 Litre Fuel Station / Fuel Point



3500 Litre Slimline Fuel Station / Fuel Point



5000 Litre Fuel Station



5000 Litre Fuel Point AGRI



7500 Litre Fuel Station



9250 Litre Fuel Station

STANDARD & OPTIONAL EQUIPMENT

70					1 9									
Standard	1300 SLFS	1400 FS	2500 SLFS	2500 FS	3500 FS	5000 FS	7500 FS	9250 FS	1300 SLFP	1400 FP	2500 SLFP	2500 FP	3500 FP	5000 FP-AGRI
4m length, 1" delivery hose with auto-shut off nozzle	4	4							v	4	4	~	~	
6m length; 1" delivery hose with auto-shut off nozzle			~	~	4	4	~	4						~
Mechanical flow meter	1	~	~	~	~	~								
LRC overfill prevention probe						4	~	~						
Tecalemit HDA Eco Fuel Management System*							4	4						
Bund Monitor						~	4	4						
Mechanical overfill prevention valve							~	4						
Lockable equipment cabinet							~	4						
2" BSP(M) fill point	4	4	~	~	4				4	~	4	4	4	~
4" lockable inspection cap	4	~	~	~	4		~	~	~	~	~	~	4	~
56L/min 230V fuel pump**	4	~	~	4	4		~	~	4	4	4	4	4	~
Large lockable access door	4	4	~	~	4	4			4	~	~	4	4	~
Bulkhead Light	4	~	~	~	~	~	~	~						
10Micron particulate & water filter	4	4	~	4	4	4	~	4						
Ultrasonic Contents Gauge with remote display	4	~	~	~	~									
Hydrostatic Contents Gauge with in-cabinet digital display						~	~	~						
2" BSP(M) offset fill point with non-return valve & lever ball valve						~	~	~						
Galvanised steel lifting eyes for ease of handling						~								
Moulded in lifting eyes				,	4		1	4	~			~	4	✓
Optional	1300 SLFS	1400 FS	2500 SLFS	2500 FS	3500 FS	5000 FS	7500 FS	9250 FS	1300 SLFP	1400 FP	2500 SLFP	2500 FP	3500 FP	5000 FP-AGRI
8m cabinet mounted automatic hose reel						~	4	4						
Mechanical flow meter									~	4	~	4	4	~
10Micron particulate filter				16					4	4	~	~	4	~
Tecalemit HDA Eco Fuel Management System*	~	~	~	~	4	4								

^{*}Low voltage tanks have a mechanical flow meter in place of the fuel management system.

TANK DIMENSIONS

Model	Length (mm)	Width (mm)	Height (mm)	Capacity (L)	Weight (Kg)	
1300 SLFS / SLFP	2300	950	1850	1344	175	
	1610	1570	1880		150	
2500 SLFS / SLFP	2550	1385	1985	2530	210	
	2060		1880		200	
3500 SLFS / SLFP	2200	2200	2060	3553	250	
	2720		2360		420	
5000 FP AGRI	2360	2360	2210			
	2940		2820		505	
9250 FS	3140	2510	2820	9382	600	

Harlequin Manufacturing

Northern Ireland 21, Clarehill Road Moira BT670PB

England Unit 1, Lancaster Business Park East Kirkby, Lincolnshire PE23 4BH

Please note: All tank capacities are brimful. All electrical installation work must be undertaken by a registered electrician.

@Harlequin. Issue: UKDT-04/2023

Please Note: Actual product colours may vary from colours shown. All information contained herein is understood to be correct at time of publication. Harlequin Manufacturing

Ltd. reserve the right to amend product specifications without notice. Please check our website for the most up to date product information.

^{**110}V, 12V, 24V fuel pumps available. 72L/min fuel pump available in 230V only.

^{*}Warranty: 10 year conditional warranty only when product is registered on our website.